




### Top View of Assembly





### SECTION A-A End View of Assembly



### SECTION B-B Side View of Assembly



### Top View Looking Inside Box



### NOTE

Purchased assembly includes lid and box made from GP ABS material and cover screws.

### 1551MFL

#### 1551MFL Enclosure


|                                        |            |
|----------------------------------------|------------|
| Black Enclosure - RAL 9011 - UL94 - HB | 1551MFLBK  |
| Gray Enclosure - RAL 7035 - UL94 - HB  | 1551MFLGY  |
| Translucent Blue - UL94 - HB           | 1551MFLTBU |

#### ACCESSORIES


Recommended Screw Torque: 15-20 ozf.in (10-15 cN.m)

|                                                                |      |             |
|----------------------------------------------------------------|------|-------------|
| Black Enclosure Cover Screws (Pkg 100)<br>X 1/2" Self Tapping] | [#4] | 1591TS100BK |
| Grey Enclosure Cover Screws (Pkg 100)<br>X 1/2" Self Tapping]  | [#4] | 1591TS100   |
| P.C. Board Screws (Pkg 100)<br>[#2 x 3/16" Self Tapping]       |      | 1551ATS100  |


### SECTION C-C Boss Heights



### Lid



### Maximum P.C. Board Size



**HAMMOND  
MANUFACTURING™**

**1551MFL**

www.hammondmfg.com